



DESCRIPTION


The L500 low-profile luminaire is available in both lensed and ambient body styles. Configured for either individual or continuous runs, the L500 LED series provides a modern, sleek design for those wanting functionality and a visually unique look. This series is perfect for applications specifying well-designed, versatile lighting.

SPECIFICATIONS


Housing:	20 gauge cold-rolled steel construction
Lengths:	4' and 8' fixtures that can also be joined for continuous rows
Finish:	Durable, low gloss, textured powder coated finish
End Caps:	Flat end cap provides a clean finish
Approvals:	UL/CUL
LED Engine:	Dimming driver and LED board combination
Optional Drivers:	Lutron, Osram, EldoLED and other options available
Distribution:	Standard 90/10 with optional distributions available
Optic:	Available in Lens or ambient
Output Package:	Super saver, high output, and very high output lumen levels available
Sensor:	Optional integrated daylight or occupancy sensors
LED Color:	Available color temperatures of 3000k, 3500k, and 4000k
Mounting:	Aircraft grade cable with fully adjustable yoke mount
Ceiling Type:	T-bar or hard ceiling mounting kits available
Battery:	Optional 12 watt constant power emergency battery
CRI:	82+
I.E.S. Data:	Available upon request
Warranty:	5-Year limited warranty

PHOTOMETRICS

* Measurements based on High level output



90/10 – Standard
 5712 lumens
 90% up - 10% down
 116 lm/W




FIXTURE OPTIONS

Ordering Example: L550-4-30-120-HO-WHT-FF

FIXTURE SERIES	LENGTH	LED COLOR	VOLTAGE	OUTPUT	EMERGENCY CIRCUIT	FINISH	INTEGRATED SENSOR	OPTIONS
L550 Lens	4	30 3000k	MVO 120-277v	SS Super Saver	Blank None	WHT	Blank None	Blank None
L520 Ambient Body	8	35 3500k 40 4000k 50 5000k	120 120v 277 277v 347 347v	HO High Output VHO Very High Output	EF Separate individual emergency feed EHF Emergency through wiring with separate feed EHS Emergency through wiring single feed with shared neutral	* Consult factory for custom colors	DAY Daylight OCC Occupancy	FF Fast blow fuse FS Slow blow fuse EB Emergency battery EC Emergency circuit

* END CAP KIT: 500-WHT (One kit required per fixture run)


L550



4' Output Package	Lumens	Watts	Lumens/Watt
Super Saver (SS)	4975	41.5	120
High (HO)	5712	49	116
Very High (VHO)	7309	67	109

* Based on 4000k

MOUNTING SUPPORT LENGTHS & FIXTURE WEIGHTS



HARDWARE ORDERING EXAMPLE: SFD-Y-15C-FA-36

PREFIX	FIXTURE ATTACHMENT	CEILING TYPE	SUSPENSION	SUSPENSION LENGTH
SFD	Single circuit feed dimmable	HC Hard ceiling	FA Fully assembled	18 24" adjustable cable
ECF	Emergency circuit feed	SC Screw set clip		24 30" adjustable cable
NP	Non-power feed	15C 15/16" tee clip		36 42" adjustable cable
	(consult factory for variations)	9C 9/16" tee clip		72 78" adjustable cable
				144 150" adjustable cable

KIT CONTENTS

- Support clips for T-bar, OR straps for J-box, with threaded stud for cable connection
- One white canopy
- Aircraft cable
- Feed cord (except non-feed hangers)
- Fixture attachment hardware

MOUNTING TYPES

